



SAFETY DATA SHEET

Latex Dry Fall Flat Black

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name Latex Dry Fall Flat Black

Product number DF-3747

Recommended use of the chemical and restrictions on use

Application Paint.

Uses advised against No specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier See Manufacturer

Contact Person Milton Arnold

Manufacturer LANCO & HARRIS CORP.
600 MID FLORIDA DRIVE
ORLANDO, FL. 32824
407-240-4000
www.lancopaints.com

Emergency telephone number

Emergency telephone Office 407-240-4000 9 – 5 eastern M_F
Chemtrec 24 Hours: 800-424-9300

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Carc. 1A - H350 Repr. 2 - H361

Environmental hazards Not Classified

Label elements

Pictogram



Signal word Danger

Hazard statements H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.

Latex Dry Fall Flat Black

Precautionary statements	P201 Obtain special instructions before use.
	P202 Do not handle until all safety precautions have been read and understood.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P308+P313 If exposed or concerned: Get medical advice/ attention.
	P405 Store locked up.
	P501 Dispose of contents/ container in accordance with national regulations.

Contains	Crystalline silica (Quartz), 2-(2-methoxyethoxy)ethanol
-----------------	---

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Limestone	30-60%
CAS number: 1317-65-3	
Classification	
Not Classified	
Crystalline silica (Quartz)	<1%
CAS number: 14808-60-7	
Classification	
Carc. 1A - H350 STOT RE 1 - H372	
2-(2-methoxyethoxy)ethanol	<1%
CAS number: 111-77-3	
Classification	
Repr. 2 - H361d	
methanol	<1%
CAS number: 67-56-1	
Classification	
Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	

The full text for all hazard statements is displayed in Section 16.

Composition comments	* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200. The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.
-----------------------------	--

4. First-aid measures

Description of first aid measures

Latex Dry Fall Flat Black

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
Skin Contact	Rinse with water.
Eye contact	Rinse with water. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Ingestion	Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Skin contact	Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
Eye contact	No specific symptoms known. May be slightly irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. This product is toxic.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

Latex Dry Fall Flat Black

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Provide adequate ventilation. Small Spillages: Collect spillage. Large Spillages: Absorb spillage with non-combustible, absorbent material. The contaminated absorbent may pose the same hazard as the spilled material. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. May cause cancer. Suspected of damaging the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions Store locked up. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class Toxic storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Limestone

Latex Dry Fall Flat Black

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction
 Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust
 Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Crystalline silica (Quartz)

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m³ respirable fraction
 A2

methanol

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m³
 Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m³
 Sk
 Long-term exposure limit (8-hour TWA): OSHA 200 ppm 260 mg/m³
 OSHA = Occupational Safety and Health Administration.
 ACGIH = American Conference of Governmental Industrial Hygienists.
 A2 = Suspected Human Carcinogen.
 Sk = Danger of cutaneous absorption.

Crystalline silica (Quartz) (CAS: 14808-60-7)

Immediate danger to life and health 50 mg/m³ 25 mg/m³

methanol (CAS: 67-56-1)

Immediate danger to life and health 6000 ppm

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Latex Dry Fall Flat Black

Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Various colors.
Odor	Mild.
Odor threshold	Not available.
pH	pH (concentrated solution): 8.5 - 9.5
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not applicable.
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Lighter than air.
Solubility(ies)	Soluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not applicable.
Specific Gravity (H₂O = 1)	1.418
Oxidizing properties	Not available.
Coating v.o.c.	7 g/l
Material v.o.c.	3 g/l

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

Latex Dry Fall Flat Black

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity May cause cancer.

IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 1
Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Suspected of damaging fertility.

Reproductive toxicity - development Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Latex Dry Fall Flat Black

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

Avoid contact during pregnancy/while nursing. May damage fertility. May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

No specific symptoms known.

Ingestion

No specific symptoms known.

Skin Contact

No specific symptoms known.

Eye contact

No specific symptoms known.

Route of entry

Ingestion Inhalation Skin and/or eye contact

Target Organs

No specific target organs known.

12. Ecological Information

Ecotoxicity

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Toxicity

Toxicity

Based on available data the classification criteria are not met.

Persistence and degradability

Persistence and degradability

The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential

No data available on bioaccumulation.

Partition coefficient

Not available.

Mobility in soil

Mobility

No data available.

Results of PBT and vPvB assessment

Other adverse effects

Other adverse effects

None known.

13. Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

Latex Dry Fall Flat Black

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

Not regulated.

Packing group**Environmental hazards**

Environmentally Hazardous Substance

No.

Special precautions for user

Not applicable.

15. Regulatory information**International Regulations****US State Regulations****California Proposition 65 Carcinogens and Reproductive Toxins**

Contains components known to the State of California to cause cancer.

methanol

Known to the State of California to cause developmental and reproductive toxicity.

Benzophenone

Known to the State of California to cause cancer.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Crystalline silica (Quartz)

Present.

Limestone

Present.

methanol

Present.

2-(2-methoxyethoxy)ethanol

Present.

Distillates (petroleum), solvent-dewaxed light paraffinic

Present.

Rhode Island "Right To Know" List

Some of the ingredients are listed or exempt.

Crystalline silica (Quartz)

Present.

Limestone

Present.

Latex Dry Fall Flat Black

methanol

Present.

Minnesota "Right To Know" List

Some of the ingredients are listed or exempt.

Crystalline silica (Quartz)

Present.

Limestone

Present.

Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated

Present.

methanol

Present.

Benzophenone

Present.

New Jersey "Right To Know" List

Some of the ingredients are listed or exempt.

2,2-dibromo-2-cyanoacetamide

Present.

Crystalline silica (Quartz)

Present.

Limestone

Present.

2-Bromo-2-(bromomethyl)pentanedinitrile

Present.

methanol

Present.

Pennsylvania "Right To Know" List

Some of the ingredients are listed or exempt.

Crystalline silica (Quartz)

Present.

Limestone

Present.

methanol

Present.

2-(2-methoxyethoxy)ethanol

Present.

Inventories

Canada - DSL/NDSL

Present.

US - TSCA

Present.

16. Other information

Training advice

Only trained personnel should use this material.

Latex Dry Fall Flat Black

Revision comments	This is first issue.
Issued by	Milton Arnold
Revision date	11/8/2016
Revision	1
SDS No.	4630
SDS status	Approved.
Hazard statements in full	H225 Highly flammable liquid and vapor. H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H350 May cause cancer. H361 Suspected of damaging fertility or the unborn child. H361d Suspected of damaging the unborn child. H370 Causes damage to organs . H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
End of SDS	XXX

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

